

LIGHTWEIGHT RMK SEAT KIT

P/N 2879089



Application

MY08-13 RMK

Before you begin, read these instructions twice and check to be sure all parts and tools are accounted for. Please retain these installation instructions for future reference and parts ordering information.

This kit includes:

<u>Qty</u>	<u>Part Description</u>	<u>Part Number</u>
1.....	Seat	2685272
1.....	Seat Support	1018789
2.....	Bolt, Carr M6	7519249
4.....	Nut, M6HXFL Nylok	7547487
2.....	Washer-6.4x18.061.6ZC	7556565
1.....	Instructions	9924078

Tools Required:

10 mm Wrench or Socket

7/16" Wrench or Socket

IMPORTANT: For your safety, and to ensure a satisfactory installation, perform all installation steps correctly in the sequence as shown on the attached instructions.

INSTALLATION INSTRUCTIONS

1. Use the 7/16" wrench or socket to remove old seat by loosening and removing nuts off the tunnel connected to the seat support. Figure 1.
2. Remove seat with attached bracket from tank and tunnel.
3. Attach new seat support to new seat as shown using the 10mm socket. Figure 2.
4. Slide seat onto bracket on tank, then install bolt, washer then nut and tighten to bolts to tunnel. Torque: 8 ft. lbs. (10.8 Nm). Figure 3.

