

PARTS LIST: SOFT TOP FIBERGLASS RODS GRAY CLIPS STRAPS WITH LOOPS

RANGER 4X4, XP, HD & CREW SOFT TOP

Note: For installation with a windshield-first install the fiberglass rods as instructed below then install the windshield following the windshield instructions and last install the top.

Optional: Place fiberglass rods through the webbing sewn to the top. Place the end of the rods into the holes in the gray plastic clips, then snap the clips on the top center section of the roll cage, so that the rods are centered side to side and go front to back. If installing with a windshield the rods need to be cut approx. 1.25" and the front clamps need to be installed in an upsidedown manner to be free from the edge of the windshield.

Open the hood.

Evenly drape the top over the frame of operators and passengers compartment. Wrap the webbing/velcro straps around the horizontal frame tubes.

Place the webbing loop into the frame tube junction above the hood panel see photo. 1. Send the webbing through the loop and cinch tight see pic. 2.

Pull the strap up and thread through the adjustable buckle attached to the front of the top. Note: Leave about 2" of excess webbing.

Wrap the rear webbing around the headrest support tube and around the outer vertical tube and back to the buckle. Thread the end of the webbing through the adjustable buckle See photo 4.

Cinch all webbing and buckle straps evenly, being sure to keep top centered. The top is designed to have a very tight fit. WARNING! Do not allow snow or water to accumulate. If problems persist install the fiberglass rods through the webbing on the top and then install the ends of the rods into the gray clips. See photo 4.

WARNING!

Remove if unit is to be trailered on public roads. CARE & CLEANING

To clean, simply rinse in cold water and allow to air dry. Do not use harsh detergents, do not machine wash or dry.

WARRANTY INSTRUCTIONS

Your new Polaris accessory is guaranteed against defects in material and workmanship

for one full year from the date of purchase. Should any problems arise, please contact

your dealer. No warranty card is necessary.





